

Mechanical Eccentric Press Machine

TAB-ECP80

???? ?????? ??????????



ش
والمعدات الصناعية
TABSH
Machine Tools

Mechanical Eccentric Press Machine

TAB-ECP80

???? ?????? ??????????

Description TAB-ECP80 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model		Unit	TAB-ECP80
Nominal Pressure		kn	800
Travel of slip block		mm	120
Frequency of travel		Frequency/minute	40
Enclosed height		mm	70
Maximum adjustment of enclosed height		mm	60
Distance from center of slip block to press body		mm	90
Size of shank holes diameter		mm	60
Bolster Surface	Front to Rear	mm	480
	Left to Right	mm	750
Size of shank holes depth		mm	70

Distance between columns		mm	300
Mold Height		mm	250
Motor Power		kw	5.5
Overall Dimensions	F.R.	mm	1790
	L.R.	mm	1420
	Height	mm	2550

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP63
???? ?????? ??????????



Mechanical Eccentric Press Machine

TAB-ECP63

???? ?????? ??????????

Description TAB-ECP63 electric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model		Unit	TAB-ECP63
Nominal Pressure		kn	630
Travel of slip block		mm	100
Frequency of travel		Frequency/minute	50
Enclosed height		mm	70
Maximum adjustment of enclosed height		mm	80
Distance from center of slip block to press body		mm	230
Size of shank holes diameter		mm	50
Bolster Surface	Front to Rear	mm	450
	Left to Right	mm	700
Size of shank holes depth		mm	70

Distance between columns		mm	370
Mold Height		mm	220
Motor Power		kw	5.5
Overall Dimensions	F.R.	mm	1800
	L.R.	mm	1500
	Height	mm	2650

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP40
???? ??????????



Mechanical Eccentric Press Machine

TAB-ECP40

???? ?????? ??????????

Description TAB-ECP40 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.


SPECIFICATIONS

Model		Unit	TAB-ECP40
Nominal Pressure		kn	400
Travel of slip block		mm	100
Frequency of travel		Frequency/minute	50
Enclosed height		mm	70
Maximum adjustment of enclosed height		mm	60
Distance from center of slip block to press body		mm	230
Size of shank holes diameter		mm	50
Bolster Surface	Front to Rear	mm	410
	Left to Right	mm	640
Size of shank holes depth		mm	70

Distance between columns		mm	320
Thickness of plate of workbench		mm	80
Mold Height		mm	230
Maximum tilt angle of press body		degree	15
Motor Power		kw	3
Overall Dimension	F.B.	mm	1400
	L.R.	mm	1200
	Height	mm	2450

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP25
???? ?????? ??????????



Mechanical Eccentric Press Machine

TAB-ECP25

???? ?????? ????????

Description TAB-ECP25 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model	Unit	TAB-ECP25
Nominal Pressure	kn	250
Travel of slip block	mm	70
Frequency of travel	Frequency/minute	40
Enclosed height	mm	70
Maximum adjustment of enclosed height	mm	60
Distance from center of slip block to press body	mm	180
Size of shank holes diameter	mm	40

Bolster Surface	Front to Rear	mm	520
	Left to Right	mm	330
Size of shank holes depth	mm		60
Distance between Uprights	mm		160
Thickness of plate of workbench	mm		170
Motor Power	kw		2.2
Overall Dimension	F.B.	mm	910
L.R.	mm		700
Height	mm		1800

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP16
???? ?????? ??????????



Mechanical Eccentric Press Machine

TAB-ECP16

???? ?????? ????????

Description TAB-ECP16 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model		Unit	TAB-ECP16
Nominal Pressure		kn	160
Strokes per Minute		Spm	110
Max.Die Height		mm	190
Die Height Adjustment		mm	40
Throat Depth		mm	160
Bolster Surface	Front to Rear	mm	280
	Left to Right	mm	450
Blanking hole		mm	100
Distance between Uprights		mm	160
Thickness of Bolster		mm	60

Inclinable Angle		degree	40
Motor Power		kw	1.5
Overall Dimension	F.B.	mm	800
	L.R.	mm	670
	Height	mm	1700

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP10
???? ?????? ??????????



Mechanical Eccentric Press Machine

TAB-ECP10

???? ?????? ??????????

Description TAB-ECP10 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model		Unit	TAB-ECP10
Nominal Pressure		kn	100
Slide Stroke		mm	50
Strokes per Minute		Spm	120
Max.Die Height		mm	150
Die Height Adjustment		mm	30
Throat Depth		mm	125
Bolster Surface	Front to Rear	mm	220
	Left to Right	mm	340

Blanking hole		mm	90
Distance between Uprights		mm	125
Thickness of Bolster		mm	50
Inclinable Angle		degree	30
Motor Power		kw	1.5
Overall Dimension	F.B.	mm	610
	L.R.	mm	550
	Height	mm	1400

header-logo

Mechanical Eccentric Press
Machine
TAB-ECP6.3
???? ?????? ??????????



Mechanical Eccentric Press Machine

TAB-ECP6.3

???? ?????? ??????????

Description TAB-ECP6.3-1 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shock-absorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

Model		Unit	TAB-ECP6.3
Nominal Pressure		kn	63
Travel of slip block		mm	40
Frequency of travel		Frequency/minute	50
Enclosed height		mm	70
Maximum adjustment of enclosed height		mm	30
Distance from center of slip block to press body		mm	190
Size of shank holes diameter		mm	70
Bolster Surface	Front to Rear	mm	200
	Left to Right	mm	340
Size of shank holes depth		mm	70

Distance between columns		mm	120
Thickness of plate of workbench		mm	30
Mold Height		mm	190
Maximum tilt angle of press body		degree	20
Motor Power		kw	0.75
Overall Dimension	F.B.	mm	400
	L.R.	mm	500
	Height	mm	1300