

All Geared Drilling Machine
SP-D3112S
??? ?????? ????? ??????



All Geared Drilling Machine

SP-D3112S

??? ?????? ????? ??????

Descriptions SP-D3112S All geared Drilling Machine New-designed, pleasing appearance, compact construction, wide speed change range, easy to operate. Easy operation with its unique workable. The working table can be rotated 180 and can be tied to +45 and -45 also it is a reliable and easy job that can be done. Equipped with a coolant system and tapping mechanism. Equipped with shortcut and overload protection, its electricity stem with powerful spindle torment is designed according to IEC standards. Characteristic protection device, small batch and mass production for drilling counter boring, reaming, tapping, spot facing, etc.

SPECIFICATIONS

model	SP-D3112S
Max.Drilling capacity (mm)	35
Diameter of column (mm)	140
Spindle travel (mm)	150
Distance spindle axis to column generating line (mm)	330
Max.Distance spindle nose to table (mm)	610
Max.Distance spindle nose to table (mm)	1150
Spindle taper	MT4
Spindle speeds range (r/min)	70-2600
Spindle speeds series	12
Spindle feeds 3 (r/min)	0.1 0.2 0.3
Dimension of worktable surface (mm)	420×420



Table travel (mm)	540
Dimension of base table (mm)	420×380
Overall height (mm)	2150
Main motor (KW)	1.5/2.2
Coolant motor (KW)	0.085
G.W/N. W (kg)	730/670

