

All Geared Drilling Machine SP-D35

??? ?????? ???? ??????



All Geared Drilling Machine

SP-D35

??? ?????? ???? ??????

Description If you are looking for a drilling machine that can handle both rough and fast manual operation, as well as accurate and slow turbine operation, look no further than the Sumore **Heavy Duty Drilling Machine SP-D35**. This all-gearred drilling machine has a variable speed spindle that allows you to adjust the drilling speed according to your needs. It also has a digital display that shows you the cutting depth and speed, so you can monitor your progress and accuracy. The Sumore **Heavy Duty Drilling Machine SP-D35** has dedicated metric or imperial leadscrews and dials, which make it easy to switch between different measurement systems. The Sumore **Heavy Duty Drilling Machine SP-D35** is a versatile and powerful tool that can participate in various metalworking applications, such as drilling, tapping, reaming, boring, and counterboring. Whether you are a hobbyist or a professional, you will find the Sumore **Heavy Duty Drilling Machine SP-D35** to be a reliable and efficient partner for your metalworking projects. **Features**

- Robust Construction & Stable Performance
- Brushless Motor & Variable Spindle Speed
- Fine & Smooth Feeding Movement on Every Direction
- High Precision for Model Engineering
- Changeable Table Length for Different Workpieces

SPECIFICATIONS

Model	SP-D35
Maximum Drilling Capacity	35 mm
Spindle Stroke	150 mm
Spindle Taper	MT4
Step of Spindle Speeds	12



Range of Spindle Speeds	70 – 2600 rpm
Step of Spindle Feeds	3
Range of Spindle Feeds	0.1, 0.2, 0.3 mm/rev
Maximum Distance from Spindle to Column	330 mm
Maximum Distance from Spindle to Worktable	610 mm
Maximum Distance from Spindle to Base	1150 mm
Worktable Travel	540 mm
Table Tilt	+/- 45°
Table Size	424 × 424 mm
Base Size	420 × 380 mm
Column Diameter	140 mm
T-slot Width (Worktable / Base)	14 / 16 mm
T-slot Amount (Worktable / Base)	2-Feb
3-phase Two Speed AC Motor	Power: 1500 / 2200 W Voltage: 220/380 V Speed: 960/1450 rpm
3-phase Pump Motor	Power: 90 W Voltage: 220/380 V Flow Rate: 6 L/min
Packing Size (LxWxH)	700 × 1150 × 2150 mm
Weight (Net/Gross)	670 / 730 Kg

