

Conventional Lathe Machine TOS SN50C ????? ??????



Image not found or type unknown



Conventional Lathe Machine

TOS SN50C

????? ?????

Description TOS SN50C Machines of outstanding performance designed for the piece and small-lot production suitable also for maintenance and repair divisions. TOS lathes are precise and reliable machines in a wide range of versions and optional accessories. **Features:**

- 1. Easy maintenance
- 2. Long lifetime
- 3. Low operating costs
- 4. Simple and ergonomic control
- 5. High turning precision
- 6. Possibility to cut all types of threads with a wide range of pitches

SPECIFICATIONS

Model	TOS SN50C
Spindle	
Front end of the spindle:	DIN B6
Spindle bore:	52 mm
Range of spindle revolutions:	22-2000 rpm
Electric Motor	
Supply voltage	3 x 400V
Frequency	60 Hz ± 2%
Main electric motor input	5.5. kW



Lathe input	6.6 kVA
Carriages	
Cross-slide lift	300 mm
Tool slide lift	140 mm
Longitudinal feed	0.05-6.4 mm/r4ev-1
Cross feed	0.025-3.2 mm/rev.-1
Longitudinal rapid feed	3000 mm/min.
Cross rapid feed	1500 mm/min.
Tailstock	
Diameter of tailstock sleeve	70 mm
Inside taper of tailstock sleeve	MT5
Lift of tailstock sleeve	180 mm
Other Dimensions	
Weight	1940 kg
Dimensions, L x W x H	3630 x 1100 x 1505 mm

