

Mechanical Eccentric Press Machine TAB-ECP6.3 ?? ?????? ????????





**** +966 55 550 7472

2 +966 12 595 4446

ALTABSH MACHINE TOOLS

RIGHTS RESERVED TO ALTABSH COMPANY 2022-2023

WWW.ALTABSH.COM | INFO@ALTABSH.COM

LOCATION: AL-JUMUM INDUSTRIAL AREA, AL-JUMUM, WESTERN REGION,

KINGDOM OF SAUDI ARABIA

@altabsh_machine





Mechanical Eccentric Press Machine TAB-ECP6.3 ??????????????

Description TAB-ECP6.3-1 eccentric press is a suitable open type of crank press featuring a left and right open type machine body (i.e., a C-shaped machine body). Its steel plate welded body has a high shockabsorbing performance. Its novel overall design gives the machine an elegant appearance. Its throat has a certain depth. The compact structure makes the use convenient and operation safe. The punch press is equipped with a turn-key rigid clutch, a cam band brake, and a press-down type safety device. Its working table is open on three sides, so the mold loading and unloading, and operation are convenient. The punch press is widely used because it provides good conditions for mechanization and automation. And as the main equipment for plate punching production, the punch press can be used for punching holes, blanking, trimming, bending, shallow stretching, and forming.

SPECIFICATIONS

| Model | | Unit | TAB-ECP6.3 |
|--|---------------|------------------|------------|
| Nominal Pressure | | kn | 63 |
| Travel of slip block | | mm | 40 |
| Frequency of travel | | Frequency/minute | 50 |
| Enclosed height | | mm | 70 |
| Maximum adjustment of enclosed height | | mm | 30 |
| Distance from center of slip block to press body | | mm | 190 |
| Size of shank holes diameter | | mm | 70 |
| Bolster Surface | Front to Rear | mm | 200 |
| | Left to Right | mm | 340 |
| Size of shank holes depth | | mm | 70 |



+966 55 550 7472 +966 12 595 4446

ALTABSH MACHINE TOOLS
RIGHTS RESERVED TO ALTABSH COMPANY 2022-2023
WWW.ALTABSH.COM | INFO@ALTABSH.COM
LOCATION: AL-JUMUM INDUSTRIAL AREA, AL-JUMUM, WESTERN REGION,

@altabsh_machine









| Distance between columns | | mm | 120 |
|----------------------------------|--------|--------|------|
| Thickness of plate of workbench | | mm | 30 |
| Mold Height | | mm | 190 |
| Maximum tilt angle of press body | | degree | 20 |
| Motor Power | | kw | 0.75 |
| Overall Dimension | F.B. | mm | 400 |
| | L.R. | mm | 500 |
| | Height | mm | 1300 |

