





Description Widely used in single or batch in the machinery manufacturing industry; instrument; building decoration and repair department. **Features:**

- 1. 32mm drilling & milling machine.
- 2. Belt driving, low noise.
- 3. The belt will skid when the machine is overloaded.
- 4. High precision.
- 5. The spindle has hand feeding and jiggle feeding.
- 6. Gear shift, friendly operation
- 7. Wide range of speed adjustment
- 8. Gear driven, gear quench high carrying capacity great torsional moment
- 9. Head rotation is operated with a bracket. Will be much more precise while beveling a hole.
- 10. High gear precision, low noise

SPECIFICATIONS

model	ZX7032
Max. Drilling capacity (mm)	31.5
Max. face mill capacity (mm)	80
Diameter of vertical milling (mm)	22
Spindle travel (mm)	130
Distance spindle axis to column generating line (mm)	202
Max. Distance spindle nose to table (mm)	460
Spindle taper	MT3



Spindle speeds range (r/min)	100~2150
Spindle speeds series	12
Dimension of worktable surface (mm)	730×210
Table travel (mm)	450×170
Overall height (mm)	1100
Main motor (W)	Single-phase:1100 Three-phase: 1500
G.W/N.W(Kg)	285/250
Packing dimension (cm)	97×77×124

